

# JIVA 5000 Series



The JIVA 5000 touch terminal series by POSIFLEX offers features such as a software controlled on/off switch to prevent accidental shutdown, optional internal UPS (uninterruptible power supply), and an integrated finger print/MSR (magnetic stripe reader) attachment. With a unique space saving stand design, all JIVA 5000 include a wall mount bracket, rear mount bracket for optional 2<sup>nd</sup> display, primary hard drive, and optional built-in battery. The base design is intended to provide POSIFLEX business partners added flexibility when installing the JIVA terminal. The JIVA 5000 series services hospitality, retail, gaming, kiosk, healthcare, c-store, petroleum, grocery and a variety of vertical markets.

**POSIFLEX™**

# JIVA 5000 Series



## All JIVA terminal models can bundle with

- SD200 series 2-in-1 attachment MSR and/or U.are.U finger print sensor
- CR4000 series Cash Drawer
- PP7000 series Aura Thermal Receipt Printer
- PD2000 series Pole Display or PD302 customer display
- KB6000 series Programmable keyboard

## Specifications

| Model   | JIVA 5715 (Thin-Client)   | JIVA 5815   |
|---|---|---|
| Max. LCD Resolution:  | 1024 x 768  |   |
| Brightness:   | 250 nit/m <sup>2</sup>  |   |
| LCD Panel:  | 15.1" dual backlit LCD panel TFT active matrix                          |   |
| Touch Sensor:   | Accutouch, resistive type   |   |
| CPU:  | C3 800GHz   | C3 1.0 GHz  |
| Memory:   | 256MB, DDR 266, SDRAM x 2 DIMM up to 1 GB                               |   |
| Video Memory:   | 16MB (expandable to 64MB)   |   |
| Audio Line Output:  | Standard (Audio Amp + Speakers option)                                  |   |
| Serial Port:  | 4 available with PS/2 touch interface                                   | With +5VDC 4 available with PS/2 touch interface, 3 available with RS232 touch controller interface |
| Parallel port:  | 1   |   |
| CR Port:  | 1 port controls 2 devices (under COM1)                                  |   |
| USB Port:   | 2   |   |
| KB Port:  | 1 x PS/2 type   |   |
| Mouse Port:   | 1 x PS/2 type   |   |
| Lan Port:   | 10/100 MHz base Ethernet  |   |
| HDD:  | N/A   | Built-in 3.5", 20GB   |
| FDD:  | 3.5" external USB interface (option)                                    |   |
| OS Support:   | WinCE   | Windows XP Professional / WEPOS   |
| Compact Flash Port:   | 1 Type II connector (compact flash memory card is option)               | N/A   |
| Internal UPS  | Yes (Battery Optional)  |   |
| ON/OFF Control:   | Software controlled for Mechanical ON/OFF or Mechanical ON Software OFF |   |
| Tilt Adjustment:  | From 17.5° to 87.5°   |   |
| Mounting Option:  | Table top or Wall mounted   |   |
| Housing Color:  | Charcoal  |   |
| Power Supply:   | AC adaptor: input 100-240V, output DC 12V/80W                           |   |
| Dimension:  | 14.8" (W)x11.1" (D) x11.7"-14.7" (H)                                    |   |
| Safety Certifications:  | PSU: UL / VDE / T mark Terminal: FCC, CE (meet IEC 100-4-2 class A)     |   |
| All JIVA terminal models come standard with integrated wall-mount bracket, rear mount bracket for optional 2 <sup>nd</sup> display, primary hard drive and optional built-in battery. |   |   |

## About POSIFLEX

POSIFLEX, has conducted business worldwide since 1984, a true engineering and design manufacturer of POS products in an ISO 9001/9002/14001 certified factory in Taiwan. POSIFLEX has been awarded 23 patents worldwide for its innovative designs. POSIFLEX integrated POS terminals and peripherals are ideal for hospitality, retail, and a growing number of vertical markets. To learn more about POSIFLEX, visit [www.posiflexusa.com](http://www.posiflexusa.com)

## JIVA 5000 series with Slim Type 4-in-1 Base Stand



Integrated wall mount bracket



Built-in primary hard drive



Rear mount bracket for optional 2<sup>nd</sup> display



Optional built-in battery

## Available Peripherals



Integrated 2-in-1 MSR attachment



Aura thermal receipt printer (PP series)



POS programmable keyboard (KB series)



Cash drawer (CR series)

**POSIFLEX™**

1280 San Luis Obispo Avenue  
Hayward, California 94544 USA  
tel : 510-429-7097  
fax : 510-475-0982  
e-mail : [sales@posiflexusa.com](mailto:sales@posiflexusa.com)  
[www.posiflexusa.com](http://www.posiflexusa.com)